

Multi-Core Shielded Cable



Cable Description

- Conductor : Stranded tinned copper(24AWG)
- Insulation : PVC/LSF/LSZH,
- Outer shield : Al-foil+Drain wire
- Sheath : PVC/LSF/LSZH
- Sheath color : Grey

Electrical Characteristics

- Rated Voltage(V) : 300V
- Operating Temperature Rated : -20℃ ~ +70℃
- Flame retardant : EN60332-1-2

Product Specification

Number of cores	mm ² per conductor	Conductor(mm)	Outer Diameter(mm)	Max conductor resistance(Ω/km)
89534	4 x 24AWG	0.20mm/7	4.50	82.3
89535	5 x 24AWG	0.20mm/7	4.80	
89536	6 x 24AWG	0.20mm/7	5.30	
89537	7 x 24AWG	0.20mm/7	5.30	
89538	8 x 24AWG	0.20mm/7	5.60	
89539	9 x 24AWG	0.20mm/7	6.20	
89540	10 x 24AWG	0.20mm/7	6.20	
89541	15 x 24AWG	0.20mm/7	7.20	
89542	20 x 24AWG	0.20mm/7	7.90	
89543	25 x 24AWG	0.20mm/7	8.60	
89544	30 x 24AWG	0.20mm/7	9.60	