


Multi-Pair Shielded Cable



Cable Description

- Conductor : Stranded tinned copper(24AWG)
- Insulation : PVC/LSZH, Twisted pair
- Outer shield : Al-foil+Drain wire
- Sheath : PVC/LSF/LSZH
- Sheath color : Grey

Electrical Characteristics

- Rated Voltage(V) : 300V
- Operating Temperature Rated : -20℃ ~ +70℃
- Flame retardant : EN60332-1-2

Product Specification

Part No.	No.of Pair ?AWG	Conductor(mm)	Outer Diameter(mm)	Max conductor resistance(Ω/km)
89502	2 x 24AWG	0.20mm/7	5.60	82.3
89503	3 x 24AWG	0.20mm/7	5.80	
89504	4 x 24AWG	0.20mm/7	6.50	
89505	5 x 24AWG	0.20mm/7	6.80	
89506	6 x 24AWG	0.20mm/7	7.30	
89507	7 x 24AWG	0.20mm/7	7.40	
89508	8 x 24AWG	0.20mm/7	8.20	
89509	9 x 24AWG	0.20mm/7	8.40	
89510	10 x 24AWG	0.20mm/7	9.30	
89515	15 x 24AWG	0.20mm/7	10.50	
89519	19 x 24AWG	0.20mm/7	11.40	
89525	25 x 24AWG	0.20mm/7	12.70	