



Submersible Cables



Cable Description

- Conductor : Strand Bare Copper
- Insulation : PVC
- Inner Sheath : PVC
- Outer Sheath : PVC
- Sheath color : Blue & Green

Electrical Characteristics

- Rated Voltage(V) : 300V/500V
- Rated Temperatur : 70 °C
- Minimum bending raduys : 10×OD

Product Specification

Part No.	No.of cores	Conductor diameter (mm)	Insulation Diameter (mm)	Inner Sheath Diameter(mm)	Outer Sheath Diameter(mm)	Max conductor resistance(Ω /km)
SC 1.5/3C	3	0.26mm×27	2.65	7.00	8.40	13.3
SC 2.5/3C	3	0.26mm×44	3.25	8.60	10.40	7.98
SC 4.0/3C	3	0.31mm×49	3.80	9.90	11.80	4.95
SC 6.0/3C	3	0.31mm×74	4.70	11.80	13.60	3.3
SC 1.5/4C	4	0.26mm×27	2.65	7.80	9.40	13.3
SC 2.5/4C	4	0.26mm×44	3.25	9.50	11.30	7.98
SC 4.0/4C	4	0.31mm×49	3.80	11.30	12.80	4.95
SC 6.0/4C	4	0.31mm×74	4.70	13.00	14.80	3.3