



SUN FAI INDUSTRIAL CO.

(WHOLLY OWNED BY GROUPIA LTD.)

www.powercord.com.hk

## Jumper Wire



### Cable Description

- Conductor : Solid Bare Copper or Solid Tinned Copper
- Insulation : PVC
- Pair Twisted

### Electrical Characteristics

- Operating Temperature Rated : -20°C ~ +80°C
- Minimum bending raduys : 7.5×OD
- Test Voltage(V) : 1000V
- Insulation DC Resistance : >50 MΩ.KM
- Abrasion Resistant

#### CW1423

Conductor (mm)	No.of cores	Insulation diameter(mm)	Maximum conductor resistance(Ω/km)
BC0.50	2	1.05	98

#### CW1321

Conductor (mm)	No.of cores	Insulation diameter(mm)	Maximum conductor resistance(Ω/km)
TC0.50	2	1.05	98

#### CW1109

Conductor (mm)	No.of cores	Outer diameter(mm)	Maximum conductor resistance(Ω/km)
TC0.40	2	0.80	148.00
TC0.50	2	0.85	95.00
TC0.60	2	0.95	65.90

#### CW1401

Conductor (mm)	No.of cores	Outer diameter(mm)	Maximum conductor resistance(Ω/km)
BC0.50	2	0.85	95