



Flexible Cable Specification

Profile	Cord Type	Temperature Rating(°C)	Approval UL CUL CSA	AWG	Overall Dimension (mm)
American Flexible Cords					
<i>Thermoplastic Cords</i>					
	TPT	60	UL CUL	27AWG/2C	2.7 X 5.4
	TST	60	UL CUL	27AWG/2C	Ø 5.7
	PXT	60	UL CUL SF	20AWG/2C	2.5 X 5.0
	TX	60	UL CUL	20AWG/2C	2.5 X 5.0
	CXTW	105	UL	22AWG	Ø 2.4
				20AWG	Ø 2.6
				18AWG	Ø 2.9
	CXTW	105	UL	22AWG/2C	2.2 X 4.6
				20AWG/2C	2.5 X 5.0
				18AWG/2C	2.7 X 5.4
	XTW	105	UL	22AWG/2C	2.2 X 4.6
				20AWG/2C	2.5 X 5.0
				18AWG/2C	2.7 X 5.4
<i>Parallel Cords Thermoplastic</i>					
	SPT-1	60, 105	UL CUL SF	20AWG/2C	2.5 X 5.0
				18AWG/2C	2.7 X 5.4
	SPT-2, SPT-2-R	60, 105	UL CUL SF	18AWG/2C	3.5 X 6.9
				16AWG/2C	3.7 X 7.5
	SPT-3	60, 105	UL CUL	18AWG/2C	4.2 X 8.4
				16AWG/2C	4.4 X 8.9
				14AWG/2C	5.9 X 10.8
				20AWG/2C	2.5 X 5.0
	SPT-1W	105	UL CUL	18AWG/2C	2.7 X 5.4
				16AWG/2C	3.5 X 6.9
	SPT-2W	105	UL CUL	18AWG/2C	3.7 X 7.5
				16AWG/2C	3.7 X 7.5
	SPT-2(Coiled)	60, 105	UL CUL SF	18AWG/2C	3.7X7.3
				16AWG/2C	3.8X7.6
	SPT-1	60, 105	UL CUL	20AWG/3C	2.5 X 6.5
				18AWG/3C	2.7 X 8.0
	SPT-2, SPT-2-R	60, 105	UL CUL SF	18AWG/3C	3.45 X 10.1
				16AWG/3C	3.7 X 11.4
	SPT-1	60, 105	UL CUL	20AWG/3C W/G	2.5 X 5.6
				18AWG/3C W/G	2.7 X 6.8
	SPT-2	60, 105	UL CUL SF	18AWG/3C W/G	3.4 X 8.6
				16AWG/3C W/G	3.7 X 9.4
	SPT-3	60, 105	UL CUL	18AWG/3C W/G	4.2 X 9.6
				16AWG/3C W/G	4.5 X 10.5
	AWM20856(Flat)	60, 105	UL	15AWG/2C	4.0 X 8.0
	AWM20856(Round)	60, 105	UL	15AWG/2C	Ø 8.1
<i>Heater Cords</i>					
	HPN, HPN-R	90, 105	UL CUL SF	18AWG/2C	3.5 X 6.9
				17AWG/2C	3.7 X 7.4
				16AWG/2C	3.9 X 7.6
	HPN	90, 105	UL CUL SF	18AWG/3C W/G	3.8 X 9.1
				16AWG/3C W/G	4.5 X 10.5
<i>Non-Integral Parallel Cords, Thermoplastic</i>					
	NISPT-1	60, 105	UL	20AWG/2C	2.8 X 5.1
				18AWG/2C	3.0 X 5.6
	NISPT-2 NISPT-2-R	60, 105	UL SF	18AWG/2C	3.7 X 7.2
				16AWG/2C	4.1 X 7.9
	NISPT-1	60, 105	UL	20AWG/3C	2.8 X 5.7
				18AWG/3C	3.8 X 8.0
	NISPT-2	60, 105	UL	18AWG/3C	3.7 X 10.8
				16AWG/3C	4.1 X 11.4