


















Flexible Cable Specification

Profile	Cord Type	Temperature Rating(°C)	Approval UL CUL CSA	AWG	Overall Dimension (mm)
Appliance Wiring Material (AWM)					
<i>Hook-UP Wire</i>					
	UL1007	80	 	30AWG 28AWG 26AWG 24AWG 22AWG 20AWG 18AWG 16AWG	Ø 1.10 Ø 1.20 Ø 1.30 Ø 1.40 Ø 1.60 Ø 1.80 Ø 2.00 Ø 2.30
	UL1013	80, 90	 	28AWG 26AWG 24AWG 22AWG 20AWG 18AWG 16AWG 14AWG 12AWG 10AWG	Ø 2.00 Ø 2.10 Ø 2.20 Ø 2.40 Ø 2.55 Ø 2.80 Ø 3.10 Ø 3.50 Ø 4.00 Ø 4.60
	UL1015	80, 90, 105	 	28AWG 26AWG 24AWG 22AWG 20AWG 18AWG 17AWG 16AWG 14AWG 12AWG 10AWG	Ø 2.00 Ø 2.10 Ø 2.20 Ø 2.40 Ø 2.55 Ø 2.80 Ø 2.90 Ø 3.10 Ø 3.50 Ø 4.00 Ø 4.60
	UL1017	80	 	20AWG 18AWG 16AWG 14AWG 12AWG 10AWG	Ø 3.35 Ø 3.60 Ø 3.90 Ø 4.30 Ø 4.80 Ø 5.40
<i>Computer Cable</i>					
	UL2464	80	 	28AWG/3C 28AWG/4C 28AWG/5C 28AWG/6C 28AWG/8C 28AWG/12C 28AWG/18C 26AWG/3C 26AWG/4C 26AWG/5C 26AWG/6C 26AWG/7C 26AWG/8C 26AWG/25C 26AWG/27C 24AWG/5C 24AWG/10C 24AWG/15C 24AWG/20C 24AWG/24C 22AWG/2C	Ø 4.00 Ø 5.00 Ø 5.00 Ø 5.00 Ø 5.00 Ø 6.00 Ø 7.40 Ø 4.50 Ø 4.50 Ø 4.50 Ø 4.50 Ø 5.00 Ø 5.00 Ø 8.60 Ø 9.00 Ø 5.90 Ø 6.80 Ø 8.00 Ø 8.50 Ø 9.50 Ø 4.20