







Flexible Cable Specification

Profile	Cord Type	Temperature Rating(°C)	Approval UL CUL CSA	AWG	Overall Dimension (mm)
<i>Flat Ribbon-Type Cable</i>					
	UL2468	80	 	28AWG/2C	1.24X2.58
				28AWG/3C	1.24X3.92
				28AWG/4C	1.24X5.26
				28AWG/5C	1.24X6.60
				28AWG/6C	1.24X7.94
				28AWG/7C	1.24X9.28
				26AWG/2C	1.34X2.78
				26AWG/3C	1.34X4.22
				26AWG/4C	1.34X5.66
				26AWG/5C	1.34X7.10
				26AWG/6C	1.34X8.54
				26AWG/7C	1.34X10.0
				24AWG/2C	1.45X3.04
				24AWG/3C	1.45X4.63
				24AWG/4C	1.45X6.22
				24AWG/5C	1.45X7.81
				24AWG/6C	1.45X9.40
				24AWG/7C	1.45X11.0
				22AWG/2C	1.62X3.34
				22AWG/3C	1.62X5.06
22AWG/4C	1.62X6.78				
22AWG/5C	1.62X8.50				
22AWG/6C	1.62X10.22				
22AWG/7C	1.62X11.94				
20AWG/2C	1.80X3.70				
18AWG/2C	2.04X4.23				
	UL2450	105	 	18AWG/2C	Ø 5.80
				18AWG/3C	Ø 6.30
				18AWG/4C	Ø 6.80